CERTIFIED LAND CORNER RECORDATION DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) Found 4" x 7" x 15" granite stone with $\frac{1}{4}$ " on west, in place. LOCATION G.L.O. record - Granite boulder, 15 x 7 x 6. Contract survey by Henry G. Hay in 1870. T.14N., R.69W. 6th P.M. DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: Set a $1\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap. At the corner: A 4" x 4" Redwood post, 4' long 18" in the ground bears SE'ly, 3 feet. Accessories: Left stone as memorial. SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.) φ S.C. See Corner Form for the C_4^1 of Sec. 4 for 1/16 corners set in the N_{2}^{\perp} of Sec. 4.

See Corner Form for the $C_{4}^{\frac{1}{4}}$ of Sec. 4 for 1/16 corners set in the $N_{2}^{\frac{1}{2}}$ of Sec. 4.

Solution:

See Corner Form for the $C_{4}^{\frac{1}{4}}$ of Sec. 4 for 1/16 corners set in the $N_{2}^{\frac{1}{2}}$ of Sec. 4.

Solution:

Not to scale Brass cap set 6" above ground.

Brass cap stamped:

T.14N. R.69W.

I, R.L. Hudson certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

S. 5 S. 4

Wyoming L.S. No. 519

Registration No.

County Clerk & Ex-Officio Register of Deeds