CERTIFIED LAND CORNER RECORDATION			
DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)			
LOCATION	Found granite boulder, 6" x tipped over.	6" x 16" with "1". Stor	ne was in ground but
1 5.24 S.19	G.L.O. record - Granite Boulder, 16 x 10 x 6 (1870)		
T.14N.	deliene locala dimino boan	401, 10 11 10 11 0 (10)	
R.69W., R.68W. 6th P.M.			
		T AND ACCESSORIES ESTABLINAL LOCATION OF THIS COR	
At the corner:	Replanted stone with "1" on	west.	
Accessories:	Raised rock mound, 2 feet SE		
SKETCH	WITH COURSE AND DISTANCE TO AD	DIACENT CORNER IF DETERMI	NED IN THIS SURVEY
SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.)			
	* 		
	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	ock Mound	
	* 		1**=40*
·	R.L. Hudson		
done on the diag	rammed corner as reported on this reco		performed or reviewed the work same.
	, a		
		Signature of Surveyor	Wyoming L.S. No. 519 Registration No.
STATE OF WYON	nd Recorder,		
County of 10	<u>vanil</u>	b .	
This "corner recor on the cross-index	d" was filed for record on the 2941 da c plat and is assigned page No14-69	y of	19 <u>73</u> , was noted
		a.)	nty Official
		Cross Index No	T. <u>68</u> R. <u>6th</u> Mer.
			T R Mer. T R Mer.
			T R Mer.
		•	T R Mer.
			T R Mer. T R Mer.

P-25 14-69

Posted. Photographed

Indexed

The State of Wyoming SS County of Laramie

This instrument was filed for record

at 354 o'clock A.M. on the

A. D. 18. 23 med dely recorded in

The Exofficio Register of Decla