State of Wyoming Corner Record

(in compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1997, Section 33—29—140, et. seq. and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.

FOUND 2" BRASS CAP IN 2" IRON PIPE 4-1/2" FOUND:

ABOVE GROUND

G.L.O. RECORD: UNKNOWN

SET: NOTHING SET

BRASS CAP

REFERENCES: SEE BELOW

DIRT



TELEPHONE PEDESTAL-2.0.* PK NAIL IN POST (TYP.) -FOUND BRASS CAP IN A IRON PIPE. 23 1974

Date of Field Work:

4/2001

Office Reference:

2-2237.00

CROSS INDEX DIAGRAM

James D. Voeller, P.E & P.L.S.

Firm/Agency, Address

A. V.I., p.c.

2035 Westland Road

Cheyenne, WY 82001

Telephone Number: (307) 637-6017

This corner record was prepared by me or under my direction and supervision. SEAL & SIGNATURE

Engineer (Civi) DATE OM

QUARTER CORNER | Section: 27|26 | T | 14 | R | 69 | ; 6th | P.M. Cross-Index No.: | R-17