


CERTIFIED LAND CORNER RECORDATION


LOCATION S.24 S.19 S.25 S.30 T.14N. R.69W., R.68W. 6th P.M.	DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) Found granite stone, 10" x 12" with 4 grooves on north and 2 grooves on south face. Stone was found planted and in fair condition. G.L.O. record - Granite Boulder, 21 x 12 x 12, 1870.
--	--

At the corner: Accessories:	DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: Set a 1 1/2" dia. x 30" long iron pipe with brass cap. Set a fence post, 3 feet NE'ly. Raised a rock mound, 3 feet SE'ly. Left stone as memorial.
--------------------------------	---

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)



Brass cap set 6" above ground.
 Brass cap stamped:
 R.69W. T.14N. R.68W.
 S.C.
 S.24 S.19
 S.25 S.30
 LS 519 1972



R.L. Hudson certify that I have carefully performed or reviewed the work done at the designated corner as reported on this recordation form and approve the same.

R.L. Hudson Wyoming L.S. No. 519
 Signature of Surveyor Registration No.

STATE OF WYOMING,
 Office of Clerk and Recorder,
 County of Saramie

This "corner record" was filed for record on the 13th day of September, 1972, was noted on the cross-index plat and is assigned page No. 14-69, in book No. ONE.

Johy B. Hillman
 County Official

Cross Index No. <u>14</u>	T. <u>68</u>	R. <u>6</u>	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.

Photographed.....

Indexed.....

Posted.....

The State of Wyoming }
County of Laramie } SS

This instrument was filed for record
at 1:57 o'clock P.M. on the

16th day of September

A. D. 19 22 and duly recorded in
Book on page

John B. Williamson

County Clerk & Ex-Officio Registrar of Deeds
By _____, Deputy