Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.

Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument.

Field Date 1-12-90 Office Reference

Found G.L.O. brass cap projecting 0.8' above ground encircled by a mound of stone and stamped as shown.

Monument Inscription

State of Wyoming Office of County Clerk County of <u>Laramie</u>

190,91,081	550. 502.
,01,90.0	00.0025 SEC. S.

This Certified Land Corner Recordation Certificate was filed for record on the _____ day of _, 19 ___, in Book No. T <u>14N</u> ___, R ______, on Alpha-Numeric coordinates and was noted on the Cross Index Plat.

	County Clerk		
Corner Type: Aliquot Corner Other	Section(s) 25,30	Meridian 6th P.M.	
Corner Name Quarter	Township 14N	Range69W Page	


Sheet ____ of ___

Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For 1/64, 1/256, 1/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

Cross Index Plat



State Plane Coordinates (optional)

Zone W NAD 1927 North (Y) =	wc	E D 1929 East (X) =	feet/meters	NAVD 1988
Latitude Scale Factor		 	Longitude	DD =
ocale racior	 	Geoid Height	7.5	

Certification						
l, <u>John</u> A. Steil	y supervision, have performed the Steil Surveying Services P.O. Box 2073 200 E. 8th Ave. Cheyenne, WY 82003 307-634-7273		certify completed this form. Action of the state of the			

Signature, Seal, and Date

Sheet ____ of ___