

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

LOCATION
 $\frac{1}{4}$
 S.25 S.30
 T.14N.
 R.69W., R.68W.
 6th P.M.

Found granite stone, 5" x 10" x 16" with " $\frac{1}{4}$ " chiseled on west face.
 Stone was found tipped over.
 G.L.O. record - Granite Boulder, 20 x 10 x 7, 1870.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the corner: Set a $\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap.
 Accessories: Set a fence post, 3 feet NE'ly.
 Left stone as memorial.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
 (May Sketch or Paste Reproduction on Reverse Side.)


$\frac{1}{4}$ cor. ● □ Post



Brass cap set 6" above ground.

Brass cap stamped:

R.69W. T.14N. R.68W.
 $\frac{1}{4}$
 S.25 S.30
 LS 519 1972



R.L. Hudson certify that I have carefully performed or reviewed the work on the diagrammed corner as reported on this recordation form and approve the same.

R.L. Hudson Wyoming L.S. No. 519
 Signature of Surveyor Registration No.

STATE OF WYOMING,
 Office of Clerk and Recorder,
 County of Saramie

This "corner record" was filed for record on the 13th day of September, 1972, was noted on the cross-index plat and is assigned page No. 14-69, in book No. ONE

Jody B. Hillman
 County Official

Cross Index No. <u>14</u>	T. <u>68</u>	R. <u>6</u>	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.