## **Wyoming Certified Land Corner Recordation Certificate**

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.

Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument.

Field Date 1-12-90 Office Reference 890 99

Found: G.L.O. brass cap projecting 1.2' above ground encircled by a mound of stone lying in fence corner N-S-E and stamped as shown.

# LARAMIE COUNTY CHEYENNE, WY.

#### State of Wyoming Office of County Clerk County of <u>Laramie</u>


This Certified Land Corner Recording 19, in E and was noted on the	300K 190. I <u>1419</u> , R 6	for record on the day of 9W, on Alpha–Numeric coordinates
		County Clerk
Corner Type:  Aliquot Corner Other	Section(s) <u>25,30,31,36</u>	Meridian 6th PM.
Corner Name <u>Section</u>	Township 14N	Range 69W Page
	Sheet of	

## Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For 1/64, 1/256, 1/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

#### **Cross Index Plat**



### **State Plane Coordinates (optional)**

Zone	w	WC	EC	E	feet/meters	 . <b>.</b>
☐ NA	D 1927		□NG	/D 1929	□ NAD 1983	NAVD 1988
North (Y) =				East (X) =	<del></del>	EL =
Latitude					Longitude	1717 ~
Scale Factor					Geoid Height	. ,

		:					
Certification							
I,	ny supervision, have performed the Steil Surveying Services	, Wyoming PLS-PE certify e-work as described above and completed this form.					
Mailing Address	P.O. Box 2073						
Street Address	200 E. 8th Ave.	Grade John A. STELL					
City, State, ZIP	Cheyenne, WY 82003	JOHN A. S. P. L. P. S. P. L. P. P. L. P. L. P.					
Telephone, FAX	307-634-7273	OM: NG					

Signature, Seal, and Date

Sheet \_\_\_\_ of \_\_