

CERTIFIED LAND CORNER RECORDATION


DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

LOCATION S.26 S.25 S.35 S.36 T.14N., R.69W. 6th P.M.	Found red granite stone, 6" x 7" x 12" with 1 groove on south and east faces. Stone was found tipped over. G.L.O. record - Granite Boulder, 16 x 10 x 6, Henry G. Hay, 1870.
--	---

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the corner: Set a 1½" dia. x 30" long iron pipe with brass cap.
 Accessories: Set a fence post, 3 feet NE'ly.
 Raised a rock mound, 3 feet SE'ly.
 Left stone as memorial.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
 (May Sketch or Paste Reproduction on Reverse Side.)



Brass cap set 6" above ground.

Brass cap stamped:

T.14N. R.69W.
 S.C.
 S.26 S.25
 S.35 S.36
 LS 519 1972



R.L. Hudson certify that I have carefully performed ~~or reviewed~~ the work done on the diagrammed corner as reported on this recordation form and approve the same.

R.L. Hudson Wyoming L.S. No. 519
 Signature of Surveyor Registration No.

STATE OF WYOMING,
 Office of Clerk and Recorder,
 County of Saramie

This "corner record" was filed for record on the 13th day of September, 1972, was noted on the cross-index plat and is assigned page No. 14-69, in book No. ONE

Jody B. Williams
 County Official

Cross Index No. _____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____

Photographed.....

Indexed.....X.....

Posted.....X.....

The State of Wyoming }
County of Laramie } SS

This instrument was filed for record
at 1:57 o'clock P.M. on the
6th day of September
A. D. 19 22 and duly recorded in
Book on page

John B. Williams

County Clerk & Ex-Officio Register of Deeds
By..... Deputy