CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) Found red granite stone, 5" x 8" x 14" with faint "1" on face. Stone was LOCATION found tipped over. 1 S.25 S.36 G.L.O. record - Granite Boulder, 15 x 8 x 5, Henry G. Hay, 1870. T.14N., R.69W. 6th P.M. DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: Set a $1\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap. At the corner: Set a fence post, 3 feet NE'ly. Accessories: Left stone as memorial. SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.) □ Post $\frac{1}{4}$ cor. 1"=10" Brass cap set 6" above surface. Brass cap stamped: T.14N. R.69W. LS 519 1972 R.L. Hudson certify that I have carefully performed or reviewed the work corner as reported on this recordation form and approve the same. Wyoming L.S. No. 519 Registration No. STATE OF WYOMING, Office of Clerk and Recorder, County of Awamul This "corner record" was filed for record on the 13th day of September on the cross-index plat and is assigned page No. 14-69, in book No. ONE Cross Index No ._ R. _ R. . _ T. _ _ T. _ _ R. .

V-23 14-69

... Mer.

T. _

_ T. _

_ R. _

_ R. _

Photographed Indexed X

Posted X

Posted X

Posted X

The State of Wyoming County of Laramie

This instrument was filed for record at Secretary o'clock Ind. M. on the A. D. 19. 2 and duly recorded in Book on page

Book on page

This instrument was filed for record at Secretary o'clock Ind. M. on the Indexed I

County Clerk & Ex-Officio Register of Deeds