

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

LOCATION $\frac{1}{4}$ S.36 S. 1 T.14N., R.69W. T.13N., R.69W. 6th P.M.	Found fine-grained granite stone, 4" x 9" x 16" with " $\frac{1}{4}$ " chiseled on north face. Stone was found in place. G.L.O. record - Granite B. [Boulder], 16 x 10 x 5, 1870.
--	--

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the corner: Set a $1\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap.
 Accessories: Set a fence post, 3 feet NE'ly.
 Left stone as memorial.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
 (May Sketch or Paste Reproduction on Reverse Side.)

\square Post
 \bullet $\frac{1}{4}$ cor.



Brass cap set 6" above ground.


Brass cap stamped:

T.14N. R.69W.

$\frac{1}{4}$ S.36
 S. 1

T.13N.

LS 519 1972



R.L. Hudson

certify that I have carefully performed ~~or reviewed~~ the work shown on the diagrammed corner as reported on this recordation form and approve the same.

R.L. Hudson
 Signature of Surveyor

Wyoming L.S. No. 519
 Registration No.

STATE OF WYOMING,

Office of Clerk and Recorder,

County of Saramie

This "corner record" was filed for record on the 13th day of September, 1972, was noted on the cross-index plat and is assigned page No. 14-69, in book No. ONE

Johy B. Hillman
 County Official

Cross Index No. <u>13</u>	T. <u>69</u>	R. <u>6</u>	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.


Photographed _____

Indexed X

Posted X

The State of Wyoming }
County of Laramie } SS

This instrument was filed for record
at 1:57 o'clock 1 M. on the
10 day of Sept in the
A. D. 19 72 and duly recorded in
Book _____ on page _____



County Clerk & Ex-Officio Register of Deeds
By _____ Deputy