CERTIFIED LAND CORNER RECORDATION DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) Found granite boulder, $6" \times 10" \times 23"$ with 6 grooves on each face. Stone was found tipped over. Found remains of rock mound. LOCATION T.14N. T.13N. G.L.O. record - Granite Boulder, 30 x 10 x 8 and a mound of stone, 1870. R.69W., R.68W. 6th P.M. (Tp. Cor.) DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: Set a $1\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap. At the corner: Set a 4" x 4" redwood witness post, scribed, 3 feet NE'ly of corner. Accessories: Rebuilt rock mound, 3 feet west of corner. Left stone as memorial. SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.) □ W.P. p. cor. Rock mound o Stone 1"=10" Brass cap set 6" above ground. Brass cap stamped: R.69W. T.14N. R.68W. S.C. S.36 S.31 S. 1 S. 6 T.13N. 1972 LS 519 R.L. Hudson certify that I have carefully performed or reviewed the work ed corner as reported on this recordation form and approve the same. Wyoming L.S. No. 519 R.L. Nanda Registration No. STATE OF WYOMING, Office of Clerk and Recorder, County of Maramil This "corner record" was filed for record on the 13th day of on the cross-index plat and is assigned page No. 14-69, in book No. ON Cross Index No 17 Mer. Т.

2-25 14-69

T.

T.

R.

R.

Mer.

Mer.

okon Dage	D. 19 and duly recorded in	le til day of Sinterching	o'clock M. on the	his instrument was filed for record	he State of Wyoming County of Laramie SS	Posted	Indexed	Photographed
-----------	----------------------------	---------------------------	-------------------	-------------------------------------	--	--------	---------	--------------

County Clerk & Ex-Officio R. gister of Decade

By Deputy