## CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

IOCATION
% Cor. 19 20
T 15 N, R 60 W
6th P.M.

Accepted 6ld fence line as east-west centerline after convering with local residences and adjacent land owners.

Also accepted road intersection to south and fence line to north after running line through and convering with local residences.

G.J.O. record - unknown

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set # 5 rebar and surv-cap at the location determined from fences, roads and testimony.

Set 1/2" pipe to northeast and southeast for witness corners, ( see sketch )

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.

(May Sketch or Paste Reproduction on Reverse Side.)

(May Sketch or Paste Reproduction on Reverse Side.)

Basis of bearing from solar observation.

Robert C. Corbet	_certify that I have carefully performed or reviewed	the work
done on the diagrammed corner as reported on this recordation form and approve the same.		
	off of the same	
	Robert C. Coefet IS 495	
	Signature of Surveyor Reg	istration No.
STATE OF WYOMING,		
Office of Clerk, and Recorder,		
County of Saramie		
This "corner record" was filed for record on the day of		
	Janet C Whitehe	ale
	County Official	
	Cross Index No. 95 T. 15 R. 60	6Mer.
	T R	Mer.
	T R	Mer.
1	T R	Mer.
	T R	Mer.
	T R	Mer.
	T R	Mer.

to

P-5 15-60

The State of Wyoming County of Laramic Indexed B..... Posted /

Photographed.

This instrument was filed for record
at 125 o clock P. M. on the
b. day of January and duly recorded in

hour Chilhitcheal

County Clerk & Ex-Officio Register of Deceds

By Deputy