State of Wyoming Corner Record (In compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1997, Section 33-29-140, et seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors) Reverse side of this form may be used if more space is needed. Record of original survey and citation of source of historical information (if corner is lost or obliterated.) Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishement of lost or obliterated corner. EVIDENCE RECORD: 1871 GLO Survey: East along the south boundary of section 35, 80.00 chains. Set a granite boulder 17"x8"x7" for corner to sections 35, 36, 1 & 2. EVIDENCE FOUND: July 2017: Granite boulder from 1871 GLO survey not found. Found a nail set 2" below T16N ground surface at intersection of two track roads extending east & south and crop lines extending north & west. Accepted as best available evidence for the corner to sections 35, **R61W** 36, 1 & 2. Set a $2\frac{1}{2}$ " aluminum cap marked as shown on a 5/8" rebar, 26" long, 7" below ground surface at position of found nail and set nail alongside. T15N 2017 ۲ _ه 1 1 4 2 3-1/4" ALUMINUM CAPPED MONUMENT PLS 2500 2-1/2" ALUMINUM CAP ON 5/8" REBAR PLS 14277 1-1/2" ALUMINUM CAPPED MONUMENT GRANITE STONE CAP ILLEGIBLE N89°21'20"E 2648.71' (M) A-21 EAST 2640.00' (R1 N89°47'16"E 5249.11' (M) EAST 5280.00' (R1) CROP LINE **LEGEND** E FOUND SECTION CORNER AS NOTED FOUND QUARTER SECTION CORNER AS NOTED (R) RECORD (1872 GLO SURVEY) TWO TRACK ROAD (RI) RECORD (1871 GLO SURVEY) 3-1/4" ALUMINUM CAP ON 5/8" REBAR PELS 13349 BASIS OF BEARING: BEARINGS AND DISTANCES ARE BASED ON A WYOMING STATE PLANE COORDINATE SYSTEM, NAD 1983, EAST ZONE, GROUND DISTANCES Date of Field Work: July 31, 2017 Office Reference: 2017-135 CROSS INDEX DIAGRAM 3 22 23 24 25 Land Surveyor / Firm / Address A This corner record was Dirk Thompson В prepared by me or under C my direction and supervision. WWC Engineering SEAL & SIGNATURE D E 1849 Terra Avenue F -10 G Sheridan, WY 82801 O ORK THOMPSULL O ORK 14277 OZ Н Telephone: (307) 672-0761 J -16 -15--14 L M N O -19 -20-P 0 R S -30--28 -27 26 T U ν w -3'2--33--34 -35 RECP #: 739878 RECORDED 10/1/2018 AT 1:32 PM BK# 2598 PG# 312 Debra K. Lee. CLERK OF LARAMIE COUNTY. WY PAGE 1 OF 1 Y. Z

В

C

D

E

G

Н

K L

M

N

0

P

0

R

S

Т

U

ν

W

X

Y

3 4 5

Corner Name

9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25

Section:

Northeast Corner

SBRPEPLS/PLSW: March 1994; PLSW January 1998

T 15N R 61W; 6TH P.M. Cross-Index No.: