Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner. Describe bound. Include condition and type of monument, accessories and ites. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument. Field Date Z-ZL-90. Office Reference Set PK Mail Whasher in Fence Corner. Found Bend # 4 & bor Burned 12 Below Surface of Gravel Real PK Mail Whashers Stomoed Whis Solid PK Mail Whashers Stomoed Whisher Solid PK Mail Wha		,				•		
evidence found. Include condition and type of monument, accessories and ries. Describe any maintenance or rebuildination performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument. Field Date 2-724-90 Office Reference Monument Inscription Set PK Nail Whasher in Rence Corner. Found Bend #4 Rebar Burned 12 Below Surface of Gravel Real PK Nail Whashers Stomoed Whis 5014 State of Wyoming Office of County Clerk Country of Laramie. This Certified Land Corner Recordation Certificate was filed for record on the day of 19 in Book No. T Recordation Certificate was filed for record on Alpha-Numeric coordinates Country Clerk Corner Type: Aliquot Corner Other Corner Name Sections Township 15N Range 43x/ Page			d in accordance v	vith W.S. 36–11–101, prii	nted in black i	ink or typed, and sh	all be for one	
Monument Inscription Set PK Nail W/Washer in Fence Corner. State of Wyoming Office of County Clerk County of Laramie. This Certified Land Corner Recordation Certificate was filed for record on the day of in Book No. T. R. on Alpha-Numeric coordinates County Clerk County Clerk Corner Type: Aliquot Corner Other Corner Name Section(s) Z. Meridian 6th. Range 63x/ Page	evidenc and ties the circ is deter original used to	the found. Include control of the tothe right, shown in the right, shown in the field note record of reestablish the control of the field in the field	ondition and type intenance or reha w monument ins oliterated, restate d; describe or corner and all	abilitation performed. In scription. If monument e the GLO or BLM show the procedure data as above for a	n /		62 HULL OG.	N. KE
Set PK Noil Whosher In Fence Corner. Set PK. Noil Whosher In Fence Corner. State of Wyoming Office of County Clerk County of	Field D	ate <u>2-26-90</u>	Office Reference	ce			3 F. CO.	OF 10712
Sch PK. Nail Whasher In Ferce Corner. State of Wyoming Office of County Clerk County of			2	*	Mo	nument Inscrip	otion	
State of Wyoming Office of County Clerk County of Laramia This Certified Land Corner Recordation Certificate was filed for record on the day of	Set PK Noil W/ Wash in Fence Corners	1	(GRAVE)	Sel PK Noil W/	eC.	ound Bent #4 = Below Surfa	Rebar Buried ace of Gravel S	Road
State of Wyoming Office of County Clerk County ofLDrDmie This Certified Land Corner Recordation Certificate was filed for record on the day of, 19, in Book No. T, R, on Alpha-Numeric coordinates	Sch PX Nail W/Washer	30-			A	III Whashers St	amoed W/LS#5	O14
This Certified Land Corner Recordation Certificate was filed for record on the day of, 19, in Book No. T, R, on Alpha-Numeric coordinates, and was noted on the Cross Index Plat. Corner Type: Section(s) Z Meridian	State Office	of County Clerk	ie					
Corner Type: Aliquot Corner Other Corner Name Section(s) Z Meridian 6 Range Range Page Page	This	Certified Land	Corner Records	ook No. T,	filed for r	ecord on the , on Alpha-Nume	day of ric coordinates	
Corner Type: Aliquot Corner Other Corner Name Section(s) Z Meridian 6 Range Range Page Page		÷				County Clerk		
Comer Name Section Township 15N Range 43W Page	• •							
Comer Name Sezzion Township 15N Range 43x Page				Section(s) Z	Merio	lian <u>6 – </u>		
		=		Township 15N	Rang	e <u>43</u> x/	Page	
				Sheet of _2_				
						=		


1511

Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For ¹/64, ¹/256, ¹/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

Cross Index Plat



Signature, Seal, and Date

State Plane Coordinates (optional)

Zone	W	WC	EC	•	E	feet/meters	
☐ NAD	1927		□NG	VD :	1929	☐ NAD 1983	☐ NAVD 1988
North (Y) =				Eas	st (X) =		EL =
Latitude						Longitude	
Scale Factor					-	Geoid Height	

Certifica	tion
IRaymond F. Connin that I, or others under my supervision, have performed the v Company or AgencyHall & Walters, Inc Mailing Address	Wyoming PLS—RR 5014 certify ork as described above and completed this form.
Street Address City, State, ZIP Telephone, FAX Street Address 873 North Cleveland Loveland, CO 80537 303-663-1177	Sonal Land Surveyor Solation 5014 Solation 5014
	Total Land
	Daig /25/Sea CO

Sheet 2 of 2