

# State of Wyoming Corner Record

(In compliance with the *CORNER PERPETUATION AND FILING ACT*, Wyoming Statutes, 1997, Section 33-29-140, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.

**G.L.O. Record:** John B. Thomas, U.S. Deputy Surveyor, 1871  
80.00 Chains Set a limestone 25 x 10 x 8


**Found:** A spike set in line with a fence west and the center line of a road lane south. The fence west was determined to follow the section line as I found the original stone 1/4 corner of Section 12 and 13 in the fence line. The distances from the spike were harmonious with found original monuments east and west.

**Set:** I removed the accepted spike and set a no. 5 x 24 ins. rebar with 2 1/2 ins. diam. alum. cap, marked as noted below, 0.75 ft. below the improved graveled access road.

From the monument:

- The north pipe of a cattleguard bears south 5.7 ft.
- A 16d nail set in a railroad tie brace post bears southeast 40.6 ft.
- A 16d nail set in the north face of a fence corner post of fences bearing south and west bears west 32.95 ft.
- The south 1/4 corner of Section 7, a stone, bears N88°50'E 2564.5 ft.
- The south 1/4 corner of Section 12, a stone, bears N89°13'W 2629.2 ft.
- The re-established northwest corner of Section 8, a 2 1/2 ins. diam. alum. cap, bears N0°15'E 5250.6 ft.

### Aluminum Cap Markings




RECORDED 12/02/2013 AT 8:56 AM REC# 628416 BK# 2368 PG# 1414  
DEBRA K. LATHROP, CLERK OF LARAMIE COUNTY, WY PAGE 1 OF 1

Date of Field Work: November 16, 2013

Office Reference: Kaiser Francis Oil: Silo Field

### CROSS INDEX DIAGRAM



Firm/Agency, Address

Paul Reid, PLS  
1533 Pinion Drive  
Cheyenne WY 82001  
307-630-2387 (C)  
307-637-3400 (O)

This corner record was prepared by me or under my direction and supervision.

*SEAL & SIGNATURE*



Corner Name: NW Corner  
SBRPEPLS/PLSW: MARCH 1994/97

Section: 18

T. 15 N., R. 63 W., 6th P.M.  
\*T. 15 N., R. 64 W., 6th P.M.

Cross-Index No.: J-1  
J-25