Wyoming Certified Land Corner Recordation Certificate

This form is to be completed in accordance with W.S. 36-11-101, printed in black ink or typed, and shall be for one individual corner.

Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a /4 16" x7"x5 found monument. Field Date 191 Office Reference R 65 W **Monument Inscription** R.P. #1 1/4 COR. GRANITE STONE 16"x7"x5 15 SEC. 12 SEC. 11 N.T.S. R.P.#2 R.P. # 3 SET 3 - RP3 - 5/61

Rebar WAIMCAP 2617
-RP - OLD FENCE R.P. #1 AZ 306-03-57, 46-71ft R.P. HZ AZ 204-36-059, 42-09ft RP #3 AZ 108-40-318, 73-94ft State of Wyoming Office of County Clerk County of LARANIE This Certified Land Corner Recordation Certificate was filed for record on the _____ day of __, 19 ___, in Book No. T _____, R ____, on Alpha-Numeric coordinates and was noted on the Cross Index Plat. **County Clerk** Meridian 6th Section(s) 11 \(\frac{1}{2} \) Corner Type: Other Aliquot Corner Range 65 WTownship 15 N Corner Name W Sheet $\sqrt{}$ of $\sqrt{}$


1, 27,

Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha–numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For 1/64, 1/256, 1/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

Cross Index Plat



State Plane Coordinates (optional)

Zone	\mathbf{W}	WC	EC	E	feet/meters		
☐ NA	D 1927		NGV	/D 1929	☐ NAD 1983	NAVD 1988	
North (Y) = _				East (X) =		EL =	
Latitude					Longitude		
Scale Factor					Geoid Height		

Certification						
I, TAMES that I, or others under my Company or Agency Mailing Address Street Address City, State, ZIP Telephone, FAX	D. VOENEZ y supervision, have performed to A.V. T ZO 35 WES Cheyence, 307 637	me work as described above and completed this form. Thand Road Wyo 92001 6017 Cate 6119				
	Sheet 2	Signature, Seal, and Date				