State of Wyoming Corner Record

(In compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1977, Section 36-11-101, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.


Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.


- FOUND LIMESTONE 10x5x15"

TOP BROKEN W/ OTHER SMALLER

BROKEN PIECES.

- REPLACED W/ 31/4 ALLIMINUM CAP BN 36" FLUMINUM PIPE STAMPED AS SHOWN. STONE AND PIECES BURICIED ALONG SIDE.





- GLO RECORD: LIMESTONE 30"X 15"X5"

LARAMIE COUNTY
CHEYENNE, WY.
'94 APR 18 PM 4 45


Date of Field Work:

3 94

Office Reference:

2712

CROSS INDEX DIAGRAM



Firm/Agency, Address

INTERMOUNTAIN PROFESSIONAL SERVICES, INC. 5801 0SAGE AVENUE CHEYENNE WY 82001

Telephone Number: (307) 632-3138

This corner record was prepared by me or under my direction and supervision.

SEAL & SIGNATURE



Corner Name: SECTION COKNER Section: [0,1] T 15 R 66; 6 P.M. Cross-Index No.: 17

BOOK 1371