CERTIFIED LAND CORNER RECORDATION DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) Found a nail with tin in graded road surface. LOCATION Found "WCCR" stones (set by County Surveyor) north and south, 40 feet 1 S. 2 4 S.11 distant. T.15N., R.67W. 6th P.M. DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: Not remonumented At the corner: Accessories: None set SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.) Basis of Bearing - By solar observation. "WCCR" Stone S 89°20' E ₹ cor. Graded Road BRANCH OF COUNTY ROAD NO. 100 "WCCR" Stone R/W Line R.L. Hudson _certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Wyoming L.S. No. 519 STATE OF WYOMING, Office of Clerk, and Recorder, County of Maramul This "corner record" was filed for record on the 19th day of on the cross-index plat and is assigned page No. 15-167, in book No. ONE County Official Cross Index No.

E-19 15-67

_ Mer.

Τ. .

T. .

T. .

_ T. _

R. .

_ R. _

_ R. _

_ R. _

Photographed - Judexed-**Postad**

The State of Wyoming County of Laramie

This instrument was filed for record

at 3.54 o'clock M. on the

A. D. 19.25 and duly recorded in

--- on page ---

Only Clerk & Ex-Officio Register of Deeds