

**CERTIFIED LAND CORNER RECORDATION**

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

LOCATION            1. Found a 3/4" dia. x 13" long iron pipe.  
                            $\frac{1}{4}$   
 S.23 S.24  
 T.15N., R.67W.,  
 6th P.M.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
 TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

1. Set a standard U.S. 2" galv. iron pipe with brass cap for corner.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.  
 (May Sketch or Paste Reproduction on Reverse Side.)



Wire fence and telephone line

34'

●  $\frac{1}{4}$  cor.



Brass cap set 6" above surface.

Brass cap stamped:

T.15N. R.67W.  
 $\frac{1}{4}$   
 S.23 S.24  
 LS 519 1972

I, R.L. Hudson certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

R.L. Hudson  
 Signature of Surveyor

Wyoming L.S. No. 519  
 Registration No.

STATE OF WYOMING,  
 Office of Clerk and Recorder,  
 County of Laramie

This "corner record" was filed for record on the 11<sup>th</sup> day of April, 1972, was noted on the cross-index plat and is assigned page No. 15-67, in book No. ONE.

Johy B. Hillman 1W  
 County Official

Cross Index No. _____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____