**CERTIFIED LAND CORNER RECORDATION** DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) LOCATION Found United States Military Reservation concrete monument with iron rod center as shown by sketch. S-34 S-35 G.L.O. record - Granite boulder,  $16 \times 8 \times 6$  (1870). S. 3 S. 2 T.15N., R.67W. T. 14N. 6th P.M. DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: No monument set. At the corner: U.S.M.R. monument bears S 0°32'35" W, 40.00 feet distant. Accessories: A  $1\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap bears N  $44^{\circ}38'05"$  W, 56.74 feet distant. From this monument a 4" x 4" Redwood post with aluminum sign bears E'ly, 1 foot distant. SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.) + 1/4 cor. PIONEER **ESTATES** 211 N 89°27'25" E 1/16 cor. Brass cap set 4" above ground. Brass cap stamped: PIONEER ESTATES U.S. M.R. mon. R.P. TO S.C. Basis of Bearing - By solar observation. S. H. 211 LS 519 1974 R.L. Hudson certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Wyoming L.S. No. 519 Registration No. STATE OF WYOMING, Office of Clerk, and Recorder, County of Janamie This "corner record" was filed for record on the 24 day of on the cross-index plat and is assigned page No.\_ 6 Mer. Cross Index No. 2 T.

Z -/7

15-67

##

. Mer. . Mer.

R.

R.

T.

T. .

Assessor.	Posted	Indexed	Photographed
_	N	A	7 <mark>g</mark>
			<

The State of Wyoming County of Laramie

This instrument was filled for record at M. on the M. D. 19 day of Haramie

A. D. 19 74 and duly recorded in Book On page

County Clerk & Ex-Officio Register of Deeds

By Deputy