

**CERTIFIED LAND CORNER RECORDATION**

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

LOCATION

$\frac{1}{4}$  S.31  
 $\frac{1}{4}$  S. 6  
 T.15N., R.69W.  
 T.14N., R.69W.  
 6th P.M.

Found 4" x 10" x 16" granite stone with " $\frac{1}{4}$ ", tipped over, badly weathered.  
 G.L.O. record - Granite boulder, 18 x 12 x 5.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
 TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the corner: Set a  $1\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap.  
 Accessories: Raised a rock mound, 2 feet north of corner monument.  
 Corner stone used to cap rock mound.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.  
 (May Sketch or Paste Reproduction on Reverse Side.)



Not to scale

Brass cap set 6" above ground.

Brass cap stamped:

T.15N. R.69W.  
 $\frac{1}{4}$  S.31  
 $\frac{1}{4}$  S. 6  
 T.14N.  
 LS 519 1972

I, R.L. Hudson certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

R.L. Hudson Wyoming L.S. No. 519  
 Signature of Surveyor Registration No.

STATE OF WYOMING,  
 Office of Clerk and Recorder,  
 County of Laramie

This "corner record" was filed for record on the 30<sup>th</sup> day of October, 1972, was noted on the cross-index plat and is assigned page No. 15-69, in book No. ONE

Johy B. Hillman

County Official

Cross Index No. <u>14N</u>	T. <u>69W</u>	R. <u>6<sup>th</sup></u>	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.

The State of Wyoming }  
County of Laramie } SS

This instrument was filed for record  
at 2:06 o'clock P. M. on the  
30th day of October,  
A. D. 1922 and duly recorded in  
Book \_\_\_\_\_ on page \_\_\_\_\_

*John B. Williams*

County Clerk & Ex-Officio Registrar of Deeds  
Deputy