

**CERTIFIED LAND CORNER RECORDATION**


DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

LOCATION $\frac{1}{4}$ S. 32 $\frac{1}{4}$ S. 5 T. 15N., R. 69W. T. 14N., R. 69W. 6th P.M.	Found 6" x 8" x 12" granite stone with " $\frac{1}{4}$ " lying on top of ground, downslope. Corner re-established by single proportionate measurement. G.L.O. record - Granite boulder, 15 x 9 x 8.
---	---

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the corner: Set a  $1\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap.  
 Accessories: Raised a rock mound south (downslope) from corner monument.  
 Left stone as memorial.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.  
 (May Sketch or Paste Reproduction on Reverse Side.)



Not to scale  
 Brass cap set 6" above ground.

Brass cap stamped:

T. 15N. R. 69W.  
 $\frac{1}{4}$  S. 32  
 $\frac{1}{4}$  S. 5  
 T. 14N.  
 LS 519 1972

I, R.L. Hudson certify that I have carefully performed ~~or reviewed~~ the work done on the diagrammed corner as reported on this recordation form and approve the same.

R.L. Hudson Wyoming L.S. No. 519  
 Signature of Surveyor Registration No.

STATE OF WYOMING,  
 Office of Clerk and Recorder,  
 County of Laramie

This "corner record" was filed for record on the 30<sup>th</sup> day of October, 1972, was noted on the cross-index plat and is assigned page No. 15-69, in book No. ONE.

John B. Williams  
 County Official

Cross Index No. <u>14N</u>	T. <u>69W</u>	R. <u>6<sup>th</sup></u>	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.