## State of Wyoming Corner Record

(in compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1977, Section 36—11—101, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors)

## Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner. GLO RECORD: NO RECORD.

MONUMENT FOUND:

NOTHING FOUND.

MONUMENT SET:

SET 5/8" X 24" REBAR WITH 2" ALUMINUM CAP IN A MOUND OF STONES. CAP STAMPED AS SHOWN BELOW.

**REFERENCES:** 

REFERENCES SHOWN BELOW.

BARBED **WIRE FENCE** 18" PINE AL.CAP 1.0' SSS S 1/16 BARBED **WIRE FENCE** Office Reference: 95131

CROSS INDEX DIAGRAM

<u>1-3-96</u>

Date of Field Work:\_

Firm/Agency, Address

STEIL SURVEYING SERVICES,LLC. 1102 WEST 19th STREET *82001* CHEYENNE

prepared by me or under my direction and supervision. SEAL & SIGNATURE

This corner record was

Telephone Number: (307) 634-7273



SOUTH 1/16 Corner Name: SBRPEPLS/PLSW: March 1994

Section: <u>30|29 T 15N R 70W; 6th P.M. Cross-Index No.: U-5</u>

0575