## Wyoming Certified Land Corner Recordation Certificate


This form is to be completed in accordance with W.S. 36–11–101, printed in black ink or typed, and shall be jor one individual corner.	
Describe below, or show in sketch attached to this form, the corner evidence found. Include condition and type of monument, accessories and ties. Describe any maintenance or rehabilitation performed. In the circle to the right, show monument inscription. If monument is determined lost or obliterated, restate the GLO or BLM original field note record; describe or show the procedure used to reestablish the corner and all data as above for a found monument.	ć
Field Date 4-13-90 Office Reference	Š
Monument set: #5 rebar with 2" aluminum RG3W RG3W RG3W RG3W RG3W RG3W RG3W RG3W	623
References: P-K nails with 1-1/2" galvanized washers stamped "5014".	
field Road 398	
State of Wyoming Office of County Clerk County of	
This Certified Land Corner Recordation Certificate was filed for record on the day of, 19, in Book No. T, R, on Alpha-Numeric coordinates, and was noted on the Cross Index Plat.	
County Clerk	
Corner Type: Section(s) <u>24</u> Meridian <u>675</u> Aliquot Corner □ Other	
Corner Name Lanter Quarter Township 16N Range 63W Page	
Sheet <u>1</u> of <u>2</u>	

## Directions for using the Cross Index Plat

Section, quarter and sixteenth corners will be marked with a dot at the corner location. The alpha-numeric coordinate number is then determined for the intersection of the two lines. A corner that applies to two or more townships shall be filed under all that apply by the use of photo copies.

Closing corners will be indexed under the township in which they control ownership. For 1/64, 1/256, 1/1024 and non-aliquot corners lying between grid designations, mark the appropriate grid area with a dot and use the index code to the north and west (local systems may be used if the method is approved by the County Surveyor or Clerk and a written description of its use is filed in the front of each book of certificates).

## **Cross Index Plat**



## State Plane Coordinates (optional)

Zone	W	WC	EC	E	feet/meters	
☐ NAD 1	1927		NGVI	1929	NAD 1983	NAVD 1988
North (Y) =			E	ast (X) =		EL =
Latitude					Longitude	
Scale Factor				·	Geoid Height	

••	Certification	on	
I,that I, or others under my	Raymond F. Connin supervision, have performed the wor		5014 certify
Company or Agency Mailing Address	Hall & Walters, Inc.		nal land
Street Address City, State, ZIP	873 North Cleveland Loveland, CO 80537		ANOND E COLLE
Telephone, FAX	303-663-1177		85° 5014 " [ 2 ]
			plik )
		( )	Date 5 2 190
	• • • • • • • • • • • • • • • • • • •		WYOMING

Signature, Seal, and Date

Sheet 2 of Z