T.16N., R.64W., 6th P.M. 1/4 Corner S.19/S.20

'93 SEP 3 AM 10 29

126086 CERTIFIED LAND CORNER RECORDATION DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) Original Survey: Alfred M. Rodgers, U.S. Deputy Surveyor, July, 1871 Record: 40.00 Chains Set a Quartz boulder 15 x 7 x 4 for 1/4 sec. cor. Found: 8-10-93 A loosely set 10 x 7 x 5 quartz stone mkd. 1/4 on west face. DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: IGN ECTW Set: No.5 x 24" rebar with 2" aluminum cap marked Monument was found in N/S fenceline and inline with latitudinal E/W fenceline along the latitudinal c-c sectionline and in conformance 45 2927 with landowner testimony (Mr. Charles Kessler) as to his father being the original homesteader knowing and building fences along the sectionlines and "half section lines". But October State was to his father being the original homesteader knowing and building fences along the sectionlines and "half section lines". But October State was to his father being SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.) Fol. Drig. Monuma Corner this record ## THIS IS A SKETCH ONLY AND DEFINITELY NOT TO ANY SCACE !! Fd. Brass CAP Basis of Bearings: Solar Observation at the NW corner Section 20, T.161 6th P.M. Paul A. Reid certify that I have careful ed the work done on the diagrammed corner as reported on this recordation form and approve 2927 Signature of Surveyor STATE OF WYOMING. Office of Clerk and Recorder, County of_ ___day of This "corner record" was filed for record on the_ __, was noted on the cross-index plat and is assigned page No.____, in book No. County Official P5 16N. R. 64W.,6thP.M. Cross Index No. 1/4 Corner T. . R.

19/20

Mer.

Mer.

Mer.

Mer.

Mer.

T.

. T. .

T. .

. T. .

. T. .

. R.

_ R. .

. R. .

_ R. _

_ R. _