

T.16N.,R.64W.,6th P.M.

Sec. Cor.

19	20
30	29

**CERTIFIED LAND CORNER RECORDATION**

**DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)**

Original Survey: Alfred M. Rodgers, U.S. Deputy Surveyor, July 1871  
Recovery: R.L. Hudson, Wyo.L.S. 519 per C.L.C.R. form this book.

**DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:**

Found the original monument 1.65' south of the R.L.Hudson Brass Cap. Stone memorial had become exposed and causing possible confusion as to true corner point. Reburied original monument east and adjacent to R.L.Hudson monument, R.L. Hudson monument being true corner point.

**SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.)**


*THIS SPACE IS INTENTIONALLY LEFT BLANK!!*

RECEIVED  
 LARAMIE COUNTY  
 CHEYENNE, WY.  
 126085  
 93 SEP 3 AM 10 29

I, PAUL A. REID certify that I have ~~carefully performed or reviewed~~ the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

2927  
Registration No.



STATE OF WYOMING,  
Office of Clerk and Recorder,  
County of \_\_\_\_\_

This "corner record" was filed for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_, was noted on the cross-index plat and is assigned page No. \_\_\_\_\_, in book No. \_\_\_\_\_.

County Official

Cross Index No. <u>R5</u>	T. <u>16N.</u>	R. <u>64W. 6th P.M.</u>	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.

19	20
30	29