

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

LOCATION

Obliterated corner.

S.32 S.33
S. 5 S. 4

See "Report of Survey" for evidence used.

G.L.O. record: Limestone, 19 x 13 x 7, Edwin James, 1870.


T.16N.,R.65W.
T.15N.,R.65W.
6th P.M.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the corner: Set 1 1/2" dia. x 30" long iron pipe with brass cap.

Accessories: Raised a rock mound, 3' NW'ly of corner monument.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.)



Brass cap set 6" above ground.

Brass cap stamped:

T.16N. R.65W.
S.C.
S.32 S.33
S. 5 S. 4

LS 519 T.15N. 1972

I, R.L. Hudson certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

R.L. Hudson
Signature of Surveyor

Wyoming L.S. No. 519
Registration No.

STATE OF WYOMING,
Office of Clerk and Recorder,
County of Laramie

This "corner record" was filed for record on the 9th day of August, 1972, was noted on the cross-index plat and is assigned page No. 16-65, in book No. 09E.

John B. Hillman
County Official

Cross Index No. <u>15</u>	T. <u>65</u>	R. <u>6th</u>	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.

The State of Louisiana }
County of L'Assomption } SS

This instrument was filed for record
at 8:59 o'clock P. M. on the
24 day of August
A. D. 19 72 and duly recorded in
Book _____ on page _____

John B. Williams

County Clerk & Ex-Officio Register of Deeds
by _____ Deputy