

# State of Wyoming Corner Record

(In compliance with the *CORNER PERPETUATION AND FILING ACT*, Wyoming Statutes, 1997, Section 33-29-140, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.

**G.L.O. Record:** Edwin James, U.S. Deputy Surveyor, July 1870



80.00 Chains Set a lime stone, 19 x 13 x 7 for corner to Sections 32 & 33 T16N R65W

**Subsequent Record:** Certified Land Corner Recordation filed by Mr. R.L. Hudson, L.S. 519, August 9, 1972, indicating "obliterated corner" and setting a 1 1/2" iron pipe with brass cap.

**Found:** 2" diam. brass cap and iron pipe as noted in the above corner record. Corner was 0.45 ft. W of a fence post of a E/W fence line and 0.9 ft. E of a N/S fence line with a scattered mound of limestones north. Ground and scattered stones were frozen at the time of recovery of this monument and I was unable to rehabilitate the mound of stone. Note monument orientation in relation to stampings was NW'ly from monuments normally set and recovered by Mr. R.L. Hudson (see north arrow below on brass cap markings diagram). Differences in my measurements and Mr. R.L. Hudson's measurements to the section corner to the north were: N0°54'E, 5298.9' (my measurement) and N0°53'20"W, 5289.1' (R.L.Hudson). My measurement from this corner to the 1/4 corner east was S89°31'E, 2647.7'.

**Set:** Nothing

**Brass Cap Markings**



RECORDED 4/23/2013 AT 4:07 PM REC# 613978 K# 2333 PG# 347  
 DEBRA K. LATHROP, CLERK OF LARAMIE COUNTY, WY PAGE 1 OF 1

Date of Field Work: March 13, 2013

Office Reference: Kaiser Francis Silo Field

**CROSS INDEX DIAGRAM**

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25																										
A																										A
B																										B
C		6		5			4			3			2			1										C
D																										D
E																										E
F																										F
G			7		8			9			10			11			12									G
H																										H
J																										J
K																										K
L		18		17			16			15			14			13										L
M																										M
N																										N
O																										O
P			19		20			21			22			23			24									P
Q																										Q
R																										R
S																										S
T			30		29			28			27			26			25									T
U																										U
V																										V
W																										W
X			31		32			33			34			35			36									X
Y																										Y
Z																										Z
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25																										

Firm/Agency, Address

Paul Reid, PLS  
 1533 Pinion Drive  
 Cheyenne WY 82001  
 307-630-2387 (C)  
 307-637-3400 (O)

This corner record was prepared by me or under my direction and supervision.

SEAL & SIGNATURE



Corner Name: SW COR. Section: 33 T. 16 N., R. 65 W., 6th P.M.,  
 SBRPEPLS/PLSW: MARCH 1994/97 T. 15 N., R. 65 W., 6th P.M.,

Cross-Index No.: Z-9  
 A-9