State of Wyoming Corner Record

(In compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1997 Section 33—29—140 et. se., and the Rules and Regulations of the Board of Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for re—establishment of lost or obliterated corner.

RECORD: G.L.O. survey by Charles H. Caton in 1873; a Limestone 14x12x4, set 10 inches deep, marked with 1/4 on north face.

RECORD: Non recorded private survey provided by PLS #2500, John Steil on 2-16-2006; found 17x13x5 inch Limestone, well set with no marks, set a 2.5 inch aluminum cap on 5/8 inch rebar 0.3 ft above ground at stone position, construct mound of stone around corner point and place original stone upside down in mound to north.

FOUND: 2.5 inch aluminum cap on 5/8 inch rebar with cap flush to ground at south edge of abandoned trail road, by PLS #2500. Corner point is on steep south slope and in cut bank of old trail road.

Re-monumentation: Nothing, comer is suspect, but held position as I do not have evidence otherwise.


NOTE: COORDINATES SHOWN ARE BASED UPON NAD83 WY EAST ZONE AND NAVD 88 VERTICAL DATUM USING GEOID 12B FROM HARN NGS PID# MN0253 "D50"

Point #	North	East	Elev.
1761101	352041.10	926666.76	5199.91

BEARINGS AND DISTANCES SHOWN HEREON ARE BASED UPON GRID USING NAD83 WYOMING EAST ZONE AND TRIMBLE R8 GPS OBSERVATION STEIL SURVEYING SKETCH Monument Location MEAS: 2671.84 2671.53 N88'42'30"E corner referenced this record = 2605.24 S89'43'45"W Steep and LARAMIE COUNTY 50.49,07 S0.28'42"E deep 2651.74 canyon 5.5.5 T17N R61W Aban<u>d</u>on Trail S = 3Road SURVEYING: 2648.09" *SURVEYING* S: *2617.68*′ 2616.88′ S 10 2.5" S0.50'19"E S0.45'18"E SLOPE Alum. cap 2006 2500 STEIL S MEAS: STEEP STEIL SURVEYING STEIL SURVEYING MEAS: 2643.01 MEAS: 2653.98 Monument Inscription 2643.33 2652.83 VERY S89'24'29"W S89'22'13"W

Date of Field Work: Oct. 16, 2019

Office Reference: DRG-21973, Pt.1761101



Firm/Agency, Address

this corner record provided by:

HAMILTON AN SURVEYING

UNDER CONTRACT TO:

RIFFIN & ASSOCIATES, INC. 1414 ELK ST., SUITE 202 ROCK SPRINGS. WY 82901 (307) 362-5028

ner record was prepared by me r my direction and supervision. SEAL & SIGNATURE



RECP #: 769471

RECORDED 1/15/2020 AT 2:04 PM BK# 2655 PG# 1760Debra K. Lee, CLERK OF LARAMIE COUNTY, WY PAGE 1 OF 1

STATE of WYOMING, Office of Clerk & Recorder, County of Laramie this block provided for county filing documentation

North one/quarter Corner Name:

, Section: 10 , T 17N , R 61W , 6th P.M., Cross-Index No.: E-15

SBRPEPLS/PLSW: March 1994; PLSW January 1998

LARAMIE County:

.Wyoming