

SW Corner Fractional Section 23, Township 17 North, Range 60 West
Field Survey completed - January 14, 1988

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

No corner evidence found. Original corner set by Henry G. Hay, November 1873.
Set a limestone 18 X 11 X 4 = 12 inches deep marked with 2 notches on the East side and
2 notches on the South side for corner to sections 22, 23, 26 and 27.

**DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:**

Construction of Wyoming State secondary #216 obliterated all evidence of the SW corner
of fractional Section 23, and at this point in time, the Wyoming Highway Department
R-O-W plats and descriptions are the best evidence of the corner's original location
and were used to determine the South boundary of Section 23. This Survey.

**SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)**

Corner not remarked this survey.

041317

RECEIVED
LARAMIE COUNTY
CHEYENNE, WY.


'88 MAR 15 PM 4 06

I, Robert W. Taylor certify that I have personally performed or reviewed the work
done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of surveyor

3891

Registration No.



STATE OF WYOMING,
Office of Clerk and Recorder,
County of Laramie

This "corner record" was filed for record on the _____ day of _____, 19____, was noted
on the cross-index plat and is assigned page No. _____, in book No. _____

County Official

Cross Index No. <u>R-17</u>	T. <u>17N</u>	R. <u>60W</u>	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.
_____	T. _____	R. _____	Mer.

BOOK 1257

2017