State of Wyoming Corner Record

(In compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1997 Section 33—29—140 et. se., and the Rules and Regulations of the Board of Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for re—establishment of lost or obliterated corner.


RECORD: U.S. LAND OFFICE survey by Edward F. Stahle from May to June 1908 0.26 chs; a closing cor. of secs. 23 and 26, a lime stone 16x3x10 ins. above ground. On true line set iron post 3ft. long, 2.75 ins. dia., 26 ins. in the ground, surmounted by brass cap, marked T.19 N., R. 60 W., S.23 on N.W.; S.26 on S.W.; WYO on W.; NEB on E." Monument was buried for county road by Nebraska Banner County Surveyor in May 1937.


FOUND: 3.2 inch brass cap on 2.75 inch iron post, cap is 10 inches below surface of state line county gravel road.

Re-monumentation: set PK nail and washers for reference points as shown in sketch.

NAD83, position:

Point #	North	East	Elev.
1860262	368228.84	961338.33	5317.01





SBRPEPLS/PLSW: March 1994; PLSW January 1998

County: LARAMIE ,Wyoming