State of Wyoming Corner Record

(In compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1977, Section 36-11-101, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost


or obliterated corner.

FOUND GRANITE STONE 6x6x6" ExposED W/ 14 CHISELED ON THE WEST.

REFERENCE POINTS SET AS SHOWN PLS 5910

GLO RECORD: GRANITE 12"x 8"x6"

Office Reference: 2717 Date of Field Work:



SEL. 5

TalesmantHIN Dot, Sou, 5801 Osuse Chegenar, WY 97001

Telephone Number: <u>309</u> 637-3/38

This corner record was prepared by me or under my direction and supervision. SEAL & SIGNATURE



Section: 5.4 T 18 R 62; 674 P.M. Cross-Index No.: 6-9 Corner Name: SBRPEPLS/PLSW:March 1994