State of Wyoming Corner Record

(In compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1977, Section 36-11-101, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.

- Found Remnants of SANDSTONE IN A MOUND OF STONES IN AN ANCIENT FENCE LINE.
- SET A Z" Aleminam CAP ON 24" #5 REBAK STAMPED AS SHOWN

PLACED Z P.K.'S W/WASHUKS IN FENCE FOR BEFERENCE SET MONUMENT AS SHOWN.

GLO RECORD: SANDSTONE 18xHx4"

F.K. S W/ WASHER IN FENCE POSTS.
PLS 5910

Date of Field Work: __________

Office Reference:_



Firm/Agency, Address

Informacitain Fro. Sov. 5001 Osnye Chescare WY Eros

Telephone Number: <u>367 632-3/38</u>

This corner record was prepared by me or under my direction and supervision.



CONNEK Section: 4,5 T 18 R 62; 67 P.M. Cross-Index No.: E-9 1528

SBRPEPLS/PLSW:March 1994 BOOK