CERTIFIED LAND CORNER RECORDATION DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) Corner falls in the South Fork of Bear Creek, not originally set. LOCATION At the witness corner, bearing North 0.50 chains, found a 5" x 12" x 22" S.6 S.5 granite stone with following marks; "WC" on west face, five grooves on S.7 S.8 south and east faces. T.18N.,R.67W. G.L.O. record (1872), "Set a granite 16 x 10 x 7 as witness for cor. to 6th P.M. Sections 5,6,7,8, as the true place for cor. comes in bed of Creek . . ." DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: At the witness corner: Set a $1\frac{1}{2}$ " dia. x 30" long galv. iron pipe with brass cap. Raised a rock mound south of witness corner. Left stone as memorial. Hub w/ tack bears N 32047° E, 221.27 feet distant. SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.) Stone 0 W.C. Top of Rock Mound 26' to creek South, 33.0 South Fork 1"=20" R.L. Hudson certify that I have carefully performed er reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Wyoming L.S. No. 519 Registration No. STATE OF WYOMING, Office of Clerk and Recorder, County of Laramie This "corner record" was filed for record on the 3.2d day of . on the cross-index plat and is assigned page No. 28-67, in book No. Cross Index No. R.

T.

T.

R.

R. ..

County Clerk & Ex-Officio Register of Deeds

By...... Deputy