State of Wyoming Corner Record

RECORDED 8/5/2020 AT 12:31 PM BK# 2687 PG# 644

Debra K. Lee, CLERK OF LARAMIE COUNTY, WY PAGE 1 OF 1

(In compliance with the *CORNER PERPETUATION AND FILING ACT*, Wyoming Statutes, 1997 Section 33—29—140 et. seq., and the Rules and Regulations of the Board of Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.

Southwest Corner, Section 11, T18N, R67W

GLO Record

SET A SANDSTONE 24x14x5 FOR COR. TO SECTIONS 10, 11, 14, 15.

Monument Description

FOUND: 15"x12"x5" (MEASURED ABOVE GROUND) SANDSTONE, FIRMLY PLANTED, WITH 4 NOTCHES ON THE SOUTH FACE, AT FENCE TEE.

LATITUDE & LONGITUDE NAD 83 (2011)

NAD 83 (2011)
BASED UPON OPUS SOLUTION

Latitude: N41°32'16.08073"


Longitude: W104°51'52.77552"

Date of Field Work: _

April 2020

132410

Cross Index Plat



Firm/Agency, Address



Topographic Land Surveyors Office Reference No.: __

Topographic Land Surveyors 340 W B St., Suite 204 Casper, WY 82601 (307) 439-4567 This corner record was prepared by me or under my direction and supervision.

SEAL & SIGNATURE



Date Prepared: <u>5/06/2020</u>

orner Name: SW Section(s): 11 T 18 N, R 67 W, 6th P.M. Laramie County, Wyoming Cross-Index No.: J-17