
State of Wyoming Corner Record

(in compliance with the CORNER PERPETUATION AND FILING ACT, Wyoming Statutes, 1977, Section 36-11-101, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Land Surveyors.)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historic information (if comer is lost or obliterated). Description of comer monumentation evidence found and/or monument and accessories established to perpetuate the location of this comer. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.





Marking on the Stone


CORNER MONUMENT SYMBOLS

- RECORD IS FOR THIS CORNER MONUMENT.
- A RELATED CORNER OR WC MONUMENT.

SCALE 1"=1000" SCALE 1"=1000"
(EXCEPT IN
TRIVIAL CASES)
BEARINGS ARE RELATED
TO WGS 84 WITH
GPS OBSERVATIONS
DRAWN BY: NJM
P.C. J. FLOYD COUNTY: LARAMIE

04/19/2009 Office Reference: Date of Field Work:_

CROSS INDEX DIAGRAM



Firm/Agency, Address

85 South 200 East

Vernal, Utah 84078

435-789-1017 Telephone Number:

This corner record was prepared by me or under my direction and supervision.

SEAL & SIGNATURE



I 1880H BENY BELEV SHAR 11887 BINN BENK (ERRA 1881) 1881

RECORDED 6/22/2009 AT 12:05 PM REC# 525078 3K# 2118 PG# 876 DEBRA K. LATHROP, CLERK OF LARAMIE COUNTY, WY PAGE 1 OF

1/4 CORNER OF MAXIMUM CONTROL Corner Name: WEST 1/4 CORNER OF SECTION 4 SBRPEPLS/PLSW: Morch 1994 (CLCR...SJA)

Section: 4 T 19N R 65W; 6TH P.M. Cross Index No.: C-9