

CERTIFIED LAND CORNER RECORDATION

LOCATION

$\frac{1}{4}$
S.18 S.17
T.19N., R.66W.
6th P.M.

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

Found 6" x 8" x 12" granite stone with " $\frac{1}{4}$ " chiseled on west face.
G.L.O. record - 16 x 10 x 4 Granite, 1872.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the corner: Set $1\frac{1}{2}$ " dia. x 30" long iron pipe with brass cap.
Accessories: Raised a rock mound, 3 feet west of corner monument.
Left stone as memorial.
A hub and tack bears S $51^{\circ}18'$ E, 1,283.5 feet distant (solar).

**SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)**

Rock Mound  $\frac{1}{4}$ cor.

 H/T



Brass cap set 6" above ground.

Brass cap stamped:

T.19N. R.66W.
 $\frac{1}{4}$
S.18 S.17
LS 519 1972

I, R.L. Hudson certify that I have carefully performed ~~or reviewed~~ the work done on the diagrammed corner as reported on this recordation form and approve the same.

R.L. Hudson
Signature of Surveyor

Wyoming L.S. No. 519
Registration No.

STATE OF WYOMING,
Office of Clerk and Recorder,
County of Sarawee

This "corner record" was filed for record on the 18th day of September, 1972, was noted on the cross-index plat and is assigned page No. 19-66, in book No. ONE.

Johy D. Stillman
County Clerk

Cross Index No. _____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____
_____	T. _____	R. _____	Mer. _____

The State of Wyoming } ss
County of Laramie

This instrument was filed for record
at 1:38 o'clock P.M. on the
18th day of September
A. D. 19 22 and duly recorded in
Book on page

John B. Williams

County Clerk & Ex-Officio Register of Deeds
By _____, Deputy