

34 | 35  
3 | 2 R70W

T20N Platte County  
T19N Laramie County

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

34 | 35  
3 | 2 T20N, T19N- R70W, found a granite stone, well set 12"x6"x8" out of ground. Marked (=) on east and (≡) on west and found a bearing tree, a pine 27" diameter to the west at 91 feet.

Record: 80 chains set a granite stone 23x10x7 from which a pine 24" in diameter bears S86°W at 140 links and pine 28" diameter bears N87°W at 199 links.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set a steel post alongside.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.)

006495  
RECEIVED  
LARAMIE COUNTY  
CHEYENNE, WY.  
'86 APR 17 PM 3 40

Bk 317/40

I, Harold O'Malley certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Harold O'Malley  
Signature of Surveyor

PE&LS 468  
Registration No.

STATE OF WYOMING,  
Office of Clerk and Recorder,  
County of \_\_\_\_\_

This "corner record" was filed for record on the 17 day of March, 1980, was noted on the cross-index plat and is assigned page No. \_\_\_\_\_, in book No. \_\_\_\_\_.

James C. Whitehead  
County Official

Cross Index No. Z17 T. 20N R. 70W 6thMer.  
A17 T. 19N R. 70W 6thMer.  
\_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
\_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
\_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
\_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
\_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.