State of Wyoming Corner Record

(In compliance with the <u>CORNER PERPETUATION AND FILING ACT</u>, Wyoming Statutes, 1997, Section 33-29-140, et. seq., and the Rules and Regulations of the Board of Registration for Professional Engineers and Professional Land Surveyors)

Reverse side of this form may be used if more space is needed.

Record of original survey and citation of source of historical information (if corner is lost or obliterated). Description of corner monumentation evidence found and/or monument and accessories established to perpetuate the location of this corner. Sketch of relative location of monument, accessories, and reference points with course and distance to adjacent corner(s) (if determined in this survey). Method and rationale for reestablishment of lost or obliterated corner.

G.L.O. Record: 80.00 Chains

A limestone 16 x 10 x 8 set 12 ins. deep marked with 1 notch on S. side and 4 notches on E. side for cor to sec's 28,29,32,33....John B. Thomas, U.S. Deputy Surveyor, August, 1874.

Found:

A well set limestone, 7" x 8" x 7" out of the ground, with 1 notch on the south edge and 4 notches on the east edge. Stone was approximately 220' south of a E/W 2 track trail road and 90' west of a small slight draw.

Set:


Nothing. Raised a small mound of stones east of the found corner.

See Map of Survey to be filed in Laramie County Clerk's Office for measurments to other found corners in the area.

ARABIR CULTITY CLERI CHETELLIE, WY. 18 APR 20 AM 9 29


Date of Field Work: March 13, 1998 Office Reference: Job No. 2-2066.98

## CROSS INDEX DIAGRAM



Firm/Agency, Address

Paul A. Reid, A.V.I. p.c. 2035 Westland Road Cheyenne, WY 82001 Telephone Number: (307)-637-6017 This corner record was prepared by me or under my direction and supervision.



Corner Name: NW Corner Section: 33 T 19N R 70W; 6TH P.M. Cross-Index No.: V-9

BOOK 1478